## Bringing tomorrow's electronics to life



# Bringing tomorrow's electronics to life



mrsisystems.com





#### **North America**

554 Clark Rd Tewksbury, MA USA 01876

Tel: +1 978 667 9449

Email: sales.mrsi@mycronic.com

#### **MRSI China**

101, Block A, Huahan Innovation Park, Langshan Road, Shenzhen, China 518057

Tel: +86 755 26414155

#### **MRSI EMEA**

(Distributor and Demo Center) Distek Strumenti & Misure Srl Via Generale Giordano Orsini 42 80123 Napoli, Italy marco@distek.it

Tel: +393483837815

MRSI Systems (a part of Mycronic Group) is the leading manufacturer of fully automated, high-speed, high-precision and flexible eutectic and epoxy die bonding systems. We offer solutions for research and development, low-to-medium volume production, and high-volume manufacturing of photonic devices such as lasers, detectors, modulators, AOCs, WDM/EML TO-Cans, Optical transceivers, LiDAR, VR/AR, sensors, silicon photonics, co-packaging optics, 3-D hybrid packaging, and optical imaging products. With 40+ years of industry experience and our worldwide local technical support team, we provide the most effective systems and assembly solutions for all packaging levels including chip-on-wafer (CoW), chip-on-carrier (CoC), PCB, and gold-box packaging. For more information visit www.mrsisystems.com

Mycronic is a Swedish high-tech company engaged in the development, manufacture and marketing of production equipment with high precision and flexibility requirements for the electronics industry. Mycronic's headquarters are located in Täby, north of Stockholm and the Group has subsidiaries in China, France, Germany, Japan, Mexico, the Netherlands, Singapore, South Korea, United Kingdom, the United States and Vietnam. Mycronic is listed on Nasdaq Stockholm. www.mycronic.com

Specifications are subject to change without notice.



## MRSI-HVM1 1 MICRON DIE BONDER



Patented turret for "on-the-fly" tool change





### **MRSI-HVM1 Applications**

#### CoS/CoC/CoB



• The MRSI-HVM1 is designed for specific applications such as: Chip-on-Carrier (CoC), Chip-on-Submount (CoS), and Chip-on-Baseplate (CoB). These assemblies use eutectic and/or epoxy stamping die bonding.

#### **Heated Head (Optional)**



• Option for a heated head on the right side, heating at a fixed temperature or pulsed heating. The left side remains the same standard MRSI-HVM1 head. This heated option is specifically designed for eutectic bonding of multiple die onto a common carrier without reflowing the neighboring solder pads.

#### AOC/PCB/GOLD-BOX



• The conveyor version is equipped with inline conveyor for single fixture or multiple cassette inputs. Large forms of carriers of the die are automatically transported, for Active Optical Cables (AOC) or similar chip-on-printed circuit board (PCB) applications, gold-box packaging, and CoC in fixture. The process options include eutectic, epoxy stamping, UV epoxy dispensing, and in-situ UV curing.

#### **Conveyor (Optional)**



• Equipped with inline conveyor for single fixture or multiple cassette inputs that can automatically transport large forms of carriers of the dies for Active Optical Cables (AOC) or similar chip-on-printed circuit board (PCB) applications, gold-box packaging, and CoC in fixture.

#### Value to our customers



- Industry leading high-speed for high-volume manufacturing
- Industry leading high-accuracy for better assembly yield and future higher density packaging
- Industry leading high-flexibility for true multi-die multi-process production in highvolume high-mix manufacturing
- Industry leading local technical support teams and application expertise
- 40+ years of experiences in industry with reliable 24/7 field operations

### MRSI-HVM1 1 Micron Die Bonder

HVM1			
CONFIGURATION	STANDARD	HEATED HEAD	CONVEYOR
APPLICATIONS			
CoC/CoS/CoB	•	•	•
CoC Silicon Photonics	•	•	•
3D Die Stacking	•	•	•
Pillar-to-Pillar Bonding	•	•	•
AOC/PCB			•
Gold Box	•		•
PROCESSES			
Multi-die, Multi-process	•	•	•
Eutectic	•	•	•
Epoxy Stamping	•	•	•
Epoxy Dispensing			•
UV Curing			•
Localized Heating		•	
Flip-chip Bonding	•	•	•
Co-planarity Bonding	•		•
FEATURES & OPTIONS			
Composite Base	•	•	•
Dual Gantry/Head	•	•	•
Heated Head (R)*		•	
Dual Ultrafast Eutectic Station	•	•	•
"On-the-fly" Patented Tool Change	(L) •	•	•
"On-the-fly" Patented Tool Change	(R) •		•
Remote Patented Auto Tool Change (R)		•	
Inline Conveyor			•
Input GP/WP & Wafer	•	•	•
Output Stage (L)	•	•	
Output Stage (R)			•

<sup>\*</sup>R=Right Side, L=Left Side